

**Product:** Mastertac Alu-Foil Floor Graphic



**Category:** Display & Visual - Solvent, Latex and UV Ink jet

**Country of Origin:** China

## Technical specifications:

PARAMETER		VALUE
Film	Materials	Alu foil
	Coating	Poly resin & powder
	Thickness	280±10 um
Glue	Type	Hi-Tac acrylic solvent
	Thickness	65 um
Liner	Type	Double PE coated paper
	Weight	120gsm
Available size	Width: 1.20m	Length: 15m
Shelf time		12 months
Storage condition	Temperature	+15°C - +24°C
	Humidity	40% - 65%
CSIRO Slip Rating		R12
Outdoor durability		6-12months (depends on the applied surface)

- Easy to apply & remove
- No shrinkage. No memory
- Specially designed for rough ground surfaces (brick, concrete, asphalt) and/or low surface energy ground/floor
- Anti-Slip & Anti-Scratch
- PVC free, 100% recyclable aluminum

### Conversion<sup>+</sup>

- |   |   |
|---|---|
| <input type="checkbox"/> Flat bed cutters     | <input type="checkbox"/> Cold overlaminating          |
| <input type="checkbox"/> Friction fed cutters | <input type="checkbox"/> Aqueous                      |
| <input type="checkbox"/> Die cutting          | <input checked="" type="checkbox"/> Latex inkjet      |
| <input type="checkbox"/> Thermal transfer     | <input checked="" type="checkbox"/> Eco Solvnt inkjet |
| <input type="checkbox"/> Screen printing      | <input checked="" type="checkbox"/> Solvent inkjet    |
| <input type="checkbox"/> Offset printing      | <input checked="" type="checkbox"/> UV curable Inkjet |

\*Always test with your combination of printer and inks prior to commercial use.

### Roll Size

1200mm x 15m	153980
--------------	--------

### Common applications

Sports event	Petrol Stations
Shop entries	Sport stadium
Traffic station signage	Museums
Parking & Garages	